

Faux Brick AS3000 Sealer



DESCRIPTION: Faux Brick AS3000 is an acrylic sealer that cures, seals, and dust proofs concrete surfaces. It offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants.

SURFACE PREPARATION: Thoroughly clean the surface prior to sealing. Use a stiff bristle brush along with concrete cleaner or household detergent to remove dirt and stains. Rinse thoroughly with garden hose or high pressure washer. After rinsing, allow 24 to 48 hours for the surface to dry before applying sealer. Failure to do so may result in white spots, poor film development and/or inadequate adhesion.

APPLICATION: Surface must be clean, free of dirt and moisture. Do not seal if surface is still wet or chance of rain is likely. Apply sealer with a solvent resistant nap roller with long handle. Use a roller pan or bucket to dip roller into. Totally saturate roller with sealer with each dip into the pan. Apply evenly with overlapping strokes to prevent bare spots. Do not puddle. Apply two (2) coats to new or unsealed surfaces for maximum protection.

TECHNICAL DATA:

Solids.....30%
Finish.....Medium - High Gloss
Coverage.....250 - 300 sq.ft. per gallon

SPECIFICATIONS:

- AASHTO M 148, Type 1, Class B
- ASTM C 309, Type 1, Class B
- ASTM C 1315, Type 1, Class A
- DRIED COATING IS USDA ACCEPTED

WARNING:

DO NOT USE ON BRICK, SLATE, STONE OR BRICK PAVERS! Due to varying porosities, early film deterioration and white spots due to loss of adhesion can occur.

Attention: This container hazardous when empty. Empty containers retain product residue (vapor and liquid). All labeled precautions must be observed. Do not re-use empty container for any purpose until commercially cleaned or reconditioned. Store empty container away from heat, sparks, and flame.

PRECAUTIONS:

Combustible Liquid (Flash point 105 degrees F)
Keep away from open flame and heat. Do not smoke.

Avoid direct contact. Skin and eye irritation may occur.

Use in well-ventilated area.

Inhalation of vapors may cause breathing difficulties.

KEEP OUT OF REACH OF CHILDREN.

For exterior use only.

FIRST AID:

Eye contact: Move victim from exposure source. Flush eyes with water for 10-15 minutes.

Skin: Remove contaminated clothing. Wash with soap and water. If irritation persists, seek medical attention.

Inhalation: Move victim to fresh air immediately. Contact a physician if breathing is difficult.

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	G

WARRANTY:

Artcrete, Inc. warrants this product to be of good quality, free of defects, and will conform with our published specifications in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, we will replace defective materials. Ninety days after Artcrete, Inc. has shipped the products, all of our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product, or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will Artcrete, Inc. be liable for a consequential damage to anyone in excess of the purchase price of the product.