

Faux Brick DC2500 Sealer



DESCRIPTION: Faux Brick DC2500 is a non-yellowing pure acrylic sealer that cures, seals, and dust proofs concrete surfaces.

DIRECTIONS: Fresh Concrete—apply after surface water has dissipated. Aged Concrete—clean surface and remove all dirt and contaminants. Apply two (2) coats for best results using sprayer or nap roller. Spraying generally will provide superior results. Do not thin or dilute.

TECHNICAL DATA:

Solids 25%
Finish.....Medium - High Gloss
Coverage.....300 - 400 sq.ft. per gallon
Drying Time (to touch).....30 minutes - 1 hour
Drying Time (traffic).....12 - 15 hours
Application Temperature.....Above 40°F

SPECIFICATIONS:

- AASHTO M 148, Type 1, Class B
- ASTM C 1315, Type 1, Class A
- DRIED COATING IS USDA ACCEPTED

WARNING:

DO NOT USE ON BRICK, SLATE, STONE OR BRICK PAVERS! Due to varying porosities, early film deterioration and white spots due to loss of adhesion can occur.

Attention: This container hazardous when empty. Empty containers retain product residue (vapor and liquid). All labeled precautions must be observed. Do not re-use empty container for any purpose until commercially cleaned or reconditioned. Store empty container away from heat, sparks, and flame.

PRECAUTIONS:

Combustible Liquid (Flash point 105 degrees F)
Keep away from open flame and heat. Do not smoke.

Avoid direct contact. Skin and eye irritation may occur.

Use in well-ventilated area.

Inhalation of vapors may cause breathing difficulties.

KEEP OUT OF REACH OF CHILDREN.

For exterior use only.

FIRST AID:

Eye contact: Move victim from exposure source. Flush eyes with water for 10-15 minutes.

Skin: Remove contaminated clothing. Wash with soap and water. If irritation persists, seek medical attention.

Inhalation: Move victim to fresh air immediately. Contact a physician if breathing is difficult.

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	G

WARRANTY:

Artcrete, Inc. warrants this product to be of good quality, free of defects, and will conform with our published specifications in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, we will replace defective materials. Ninety days after Artcrete, Inc. has shipped the products, all of our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product, or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will Artcrete, Inc. be liable for a consequential damage to anyone in excess of the purchase price of the product.