

## Moving Companyweb Databases Version 1.00

By default, the companyweb installation has two databases: STS\_Config and STS\_<servername>\_1. Each of which needs to be moved using the following steps:

1. Log onto the SBS Server and go *Start | Run | CMD* to open DOS prompt.
2. Type the following command to stop the web server:

```
iisreset /stop
```

3. Next stop the Sharepoint Timer service:

```
net stop sptimer
```

4. Next launch the OSQL utility to manage MSDE:

```
osql -E -S %computername%\SharePoint
```

5. Use the following commands to detach the default configuration database:

```
EXEC sp_detach_db 'STS_Config', 'true'  
GO
```

6. Use the following command to detach the default content database:

```
EXEC sp_detach_db 'STS_<servername>_1', 'true'  
GO
```

7. Move both the configuration and content databases to their new location. Be sure to move both the database (.mdf) and transaction log (.ldf) files for each database.

8. To attach the configuration database, enter the following:

```
EXEC sp_attach_db 'STS_Config',  
'<new_path>\STS_Config-mdf', '<new_path>\STS_config_Log.ldf'  
GO
```

9. To attach the content database, enter the following command:

```
EXEC sp_attach_db 'STS_<servername>_1',  
'<new_path>\STS_<servername>_1.mdf','<new_path>\STS_<server  
name>_1_log.ldf'  
GO
```

10. Exit the OSQL utility by pressing CTRL+C
11. Restart the Sharepoint Timer service:

```
net start sptimer
```

12. Restart web server

```
iisreset /start
```