



Shown in: Natural Wood

WWW.MALARKEYROOFING.COM

| ANTIQUE BROWN BLACK   | OAK TEG                  |  |
|---|--------------------------|--|
|   | Featuring *              | SCOTCHGARD <sup>™</sup> PROTECTION FROM 3M<br>Regions that are prone to algae growth should inquire about our Legacy <sup>®</sup> shingles<br>featuring the Scotchgard <sup>™</sup> protection from 3M. The Legacy <sup>®</sup> shingles, featuring<br>the 20-year Scotchgard <sup>™</sup> Algae Resistant Roofing System warranty from 3M, are<br>equipped with the most effective solution available against algae staining.                   |
| HEATHER MIDNIGHT  | BLACK                    | <b>EXTREME WEATHER PROTECTION</b><br>Legacy <sup>®</sup> provides a durable barrier against extreme weather, receiving the<br>UL 2218 Class 4 Impact Resistance classification, the highest rating possible.   |
|   |                          | In a Class 4 rating test, the Legacy <sup>®</sup> withstood a simulation of hailstones impacting a roof at 90 mph (144 kph) without sustaining damage.   |
| NATURAL WOOD  | GREY                     | <b>RUGGED DURABILITY</b><br>Malarkey's revolutionary Legacy <sup>®</sup> shingle technology begins with a durable base<br>layer of fiberglass mat. Malarkey's unique fiberglass mat is coated on both sides<br>with SBS enhanced asphalt, which provides tensile strength and increased flexibility,<br>protecting your investment.  |
|   | CERT (SBS)               | <b>SBS MODIFIED ASPHALT</b><br>The rubberizing aspect of SBS increases flexibility and weatherability for your<br>roof. The thermo cycling resilience of SBS enhanced asphalt provides greater<br>granule adhesion for the shingle to create a better barrier from the elements. When<br>granules stay on the shingles, your roof lasts longer.  |
| RAINFOREST  |                          | <b>ZONE®</b><br>One of the most critical aspects of a successful roofing project is correct shingle<br>installation. Improper fastener placement is the leading cause of incorrect shingle<br>installation and can subsequently void the warranty.   |
|   | ZONE                     | Legacy <sup>®</sup> is manufactured using the patented ZONE <sup>®</sup> technology that includes<br>a tapered nailing area over three times larger than other laminate shingles. The<br>ZONE's <sup>®</sup> larger nailing area dramatically improves correct fastener placement.   |
| SILVERWOOD STORM  | GREY GREY                | <b>RAIN SEAL PROTECTION</b><br>Malarkey's Legacy <sup>®</sup> shingle is manufactured with a double line of defense in the<br>critical area for a laminated shingle, with double SEBS asphalt rain seal protection.  |
|   | RAIN SEAL<br>PROTECTION  | The SEBS asphalt has elongation capabilities up to 800 percent and is flexible down<br>to 0°F (-18°C). The rain seal remains intact through the freeze and thaw cycle.<br>Malarkey's SEBS asphalt adhesive is superior to oxidized asphalt because of its<br>cohesive and adhesive properties. The adhesive properties of SEBS asphalt join the<br>shingle together while the cohesive properties prevent it from breaking apart from<br>itself. |
|   |                          | LIMITED WIND WARRANTY  |
| WEATHERED WOOD  | LIMITED WIND<br>WABBANTY | Legacy* shingles come with a 110 mph (177 kph) Limited Wind Warranty.  |
|   | 2                        | Legacy <sup>®</sup> shingles are eligible for a 130 mph (209 kph) Enhanced Wind Warranty   |
|   | ENHANCED WIND            | when Malarkey's Smart Start <sup>™</sup> shingle is installed, shingles are six nailed, and one<br>or more of Malarkey's supporting products – Arctic Seal <sup>®</sup> , Right Start <sup>™</sup> UDL,  |
|   | WARRANTY                 | SecureStart, <sup>™</sup> EZ-Ridge <sup>™</sup> (8 <sup>n</sup> , 10 <sup>n*</sup> ) or Hip & Ridge Strips (10 <sup>n</sup> , 12 <sup>n*</sup> ) <sup>**</sup> – are used.   |
| δ   |                          | • ASTM D7158 Class H • ASTM D3462  |
| FEATURING   |                          | • ASTM D3161 Class F • ASTM D3018 Type I   |
| Limited Lifetime Shingle W 15 year Pight Start <sup>™</sup> Warre |                          | ASTM E108 Class A UL 2218 Class 4 CCA A123 5 CCA A123 5 CCA A123 5   |

• CSA A123.5

• FBC Approval – #14809

• 15-year Right Start<sup>™</sup> Warranty

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Limited warranties carry terms and conditions. Contact your local Malarkey representative for further information. See Malarkey Shingle Warranty for details.

 $\delta$  For complete Limited Lifetime Warranty details, reference Malarkey's Limited Lifetime Shingle Warranty. \*Malarkey Roofing systems require algae resistant EZ-Ridge™ shingles or 10"& 12" Hip and Ridge shingles, in conjunction with the algae resistant shingles, to receive the full 20-year algae resistant system warranty. The Alaskan® featuring Scotchgard<sup>™</sup> Algae Resistant Protection from 3M can be substituted as hip and ridge shingles, in conjunction with the algae resistant shingles, to receive the full 20-year algae resistant system warranty. 3M and Scotchgard are trademarks of 3M Company. \*\*Some contractors adapt roofing shingles for use as a hip and ridge shingle. If your contractor uses this method, the Enhanced Wind Warranty will apply when The Alaskan<sup>®</sup> is used as hip and ridge shingles. Use of Dura-Seal<sup>™</sup> shingles for hip and ridge will not qualify toward Enhanced Wind Warranty.

This version supersedes all previous versions. Rev. 5/14



• ICC Approval – ESR 3150