

# M15D AllroundDual Camera



LEFT Sensor



RIGHT Sensor

## Robust. Most Advanced Design.

The M15D features two light-sensitive image sensors and two lenses that allow the camera to generate sharp color videos and high-contrast B&W videos, even in dark situations. The electronic switching between the day and night system is automatic, with no moving parts and is based on light conditions to ensure reliable operation at any temperature and in any weather.

10

from \$1,330

### Intelligent Dual-Lens Surveillance

Along with an integrated microphone, speaker and sensor to record the ambient temperature, the weatherproof housing (IP66) features automatic recording onto SD cards and secure video motion analysis (MxActivitySensor) with alarm messaging.



### Fast, Cost-Effective Installation

The M15D ships as a complete kit, including wall & ceiling mounts and other mounting accessories. As with all MOBOTIX cameras, no additional software, housings or cooling/heating fans are required.

**IP66**
**140°F**  
**-22°F**

### Robust Design

By design, the M15D is the most robust of the entire MOBOTIX range of products. With an IP66 weatherproof rating, it can withstand extreme temperatures and the harshest of conditions.



### Fully Integrated Future-proof System

The all-in-one sensor modules can be swapped out within minutes, thanks to our new modular hardware platform. The integrated locking system ensures the sensor modules remain fixed in place.

**from \$268**

## Technical Data

Technical Data			
<b>Models</b>	Sec	<b>Lens Options</b>	L10 to L270
<b>Image Sensors</b>	1/1,8" CMOS (6MP)	<b>Sensor Resolution</b>	6MP: 3072x2048 pixels (Color/B&W)
<b>Max. Frame Rate</b> (MxPEG)	MEGA/HD: 30 fps, QXGA: 15 fps, 6MP: 8 fps (2x 6MP: 4 fps)	<b>Compression</b>	MxPEG, M-JPEG, JPEG, H.264 (SIP video)
<b>DVR Recording</b>	Internal: microSD Card External: PC/NAS (to 4 TB)	<b>Audio</b>	Integrated microphone & speaker, VoIP, intercom, sound recording
<b>Operating Conditions</b>	IP66, IK06, -30 to +60 °C/-22 to +140 °F	<b>Internal Sensors</b>	Temperature, PIR, microphone illumination, shock detector
<b>Image Processing</b>	MxActivitySensor, VMD, image correction, backlight	<b>Software</b> (free of charge)	MxManagementCenter, MxControlCenter, MxEasy, MOBOTIX App

### M15D – Reliable Even Under Extreme Conditions

The M15D camera is certified according to IP66 and has been successfully tested in a temperature range of -30 to +60 °C/-22 to +140 °F. In line with the proven MOBOTIX product strategy, the M15D model does not require additional cooling, heating or a special housing, and only five watts to be fully operational.